

AIM LCR

Pivoting In-Wall Home Theater Speakers



With the flat-panel revolution changing the way we watch TV, customers are looking for elegant ways to improve the audio side of the equation as well. The AIM LCR series is a flush-mounted in-wall with dual 5¼-inch woofers in a fully pivoting baffle in a D'Apollito configuration bracketing a 1-inch pivoting tweeter. Designed to mount vertically or horizontally, the AIM LCRs will fit sideways in a standard stud bay.

The AIM LCR's create a spectacular soundstage for music or film with the ability to produce every nuance of a performance. Their pivoting baffles allow them to be toed-in from left and right and adjusted vertically if in the horizontal position.

AIM
CINEMA SERIES

AIM LCR In-Wall Speakers

AIM LCR 5

Order Stock # ASM84651

- Pivoting Woofer Baffle
- Two 5¼" Kevlar Cone Woofers with Phase Plugs
- Pivoting 1" Aluminum/Magnesium Dome Tweeter
- Front-Mounted Switches Allow for up to ±3dB of Bass and Treble Adjustment
- Timbre-Matched to All Five Series Speakers

Efficiency: 91dB 1W/1m
Power Handling: 5 - 100 Watts
Impedance: 8/6 Ohms, Depending on Switch Settings
Frequency Response: 48Hz - 20kHz ±3dB
Dimensions: (H x W x D) 9½" x 17½" x 4" (235 mm x 443 mm x 102 mm)
Wall Cut-Out: (H x W) 7½" x 14½" (190 mm x 362 mm)



Patent Pending



AIM LCR 3

Order Stock # ASM84631

- Pivoting Woofer Baffle
- Two 5¼" Aluminum/Magnesium Cone Woofers with Phase Plugs
- Pivoting 1" Aluminum/Magnesium Dome Tweeter
- Front-Mounted Switches Allow for up to ±3dB of Bass and Treble Adjustment
- Timbre-Matched to All Three/Four Series Speakers

Efficiency: 90dB 1W/1m
Power Handling: 5 - 100 Watts
Impedance: 8/6 Ohms, Depending on Switch Settings
Frequency Response: 50Hz - 20kHz ±3dB
Dimensions: (H x W x D) 9½" x 17½" x 4" (235 mm x 443 mm x 102 mm)
Wall Cut-Out: (H x W) 7½" x 14½" (190 mm x 362 mm)



Patent Pending



AIM LCR 1

Order Stock # ASM84611

- Pivoting Woofer Baffle
- Two 5¼" Injection Molded Graphite Cone Woofers with Phase Plugs
- Pivoting 1" Silk Dome Tweeter
- Timbre-Matched to All One Series Speakers

Efficiency: 89dB 1W/1m
Power Handling: 5 - 80 Watts
Impedance: 8 Ohms
Frequency Response: 55Hz - 20kHz ±3dB
Dimensions: (H x W x D) 9½" x 17½" x 4" (235 mm x 443 mm x 102 mm)
Wall Cut-Out: (H x W) 7½" x 14½" (190 mm x 362 mm)



Patent Pending

