

AIM LCR3

Pivoting In-Wall Home Theater Speakers



Taking advantage of the research and development resources invested in the original AIM LCR, we have created a sibling with a much smaller footprint. The AIM LCR3 is a two-way D'Appolito design with dual 3-inch woofers sandwiching a pivoting 3/4-inch dome tweeter. As with the original AIM LCR, this speaker features a fully pivoting baffle to allow the installer to focus the sound toward the listening area.

Available in three models, the AIM LCR3 is perfect for small theater applications as well as any situation that requires a flush-mounted speaker that will fit into a very small space like a soffit. Add a subwoofer to fill in the bottom end, and you will be impressed with the amount of sound these diminutive little speakers can produce.



AIM LCR3 In-Wall Speakers

AIM LCR3 Five


Order Stock # ASM74351

- Pivoting Woofer Baffle
- Two 3" Kevlar® Cone Woofers with Phase Plugs
- Pivoting 3/4" Aluminum/Magnesium Dome Tweeter
- Front-Mounted 2-Position Treble Adjustment Switch
- Timbre-Matched to All Five Series Speakers

Efficiency: 86dB 1W/1m
Power Handling: 5 - 60 Watts
Impedance: 8 Ohms Compatible
Frequency Response: 60Hz - 20kHz ±3dB
Dimensions: (H x W x D) 10" x 5 1/2" x 3" (254 mm x 146 mm x 76 mm)
Wall Cut-Out: (H x W) 9" x 4 3/4" (227 mm x 120 mm)



Patent Pending



AIM LCR3 Three

Order Stock # ASM74331

- Pivoting Woofer Baffle
- Two 3" Aluminum Cone Woofers with Phase Plugs
- Pivoting 3/4" Aluminum Dome Tweeter
- Front-Mounted 2-Position Treble Adjustment Switch
- Timbre-Matched to All Three Series Speakers

Efficiency: 86dB 1W/1m
Power Handling: 5 - 60 Watts
Impedance: 8 Ohms Compatible
Frequency Response: 78Hz - 20kHz ±3dB
Dimensions: (H x W x D) 10" x 5 1/2" x 3" (254 mm x 146 mm x 76 mm)
Wall Cut-Out: (H x W) 9" x 4 3/4" (227 mm x 120 mm)



Patent Pending



AIM LCR3 One

Order Stock # ASM74311

- Pivoting Woofer Baffle
- Two 3" Injection Molded Graphite Cone Woofers with Phase Plugs
- Pivoting 3/4" Silk Dome Tweeter
- Timbre-Matched to All One Series Speakers

Efficiency: 85dB 1W/1m
Power Handling: 5 - 60 Watts
Impedance: 8 Ohms Compatible
Frequency Response: 80Hz - 20kHz ±3dB
Dimensions: (H x W x D) 10" x 5 1/2" x 3" (254 mm x 146 mm x 76 mm)
Wall Cut-Out: (H x W) 9" x 4 3/4" (227 mm x 120 mm)



Patent Pending

