

AIM Cinema Dipole

In-Wall Home Theater Speakers



Creating a diffused sound field for rear channel surround has become critical to mimic the array of speakers along the side and back walls of a traditional movie theater. The new AIM Dipole does this in a very elegant format.

Each speaker has two 5 1/4-inch drivers and two 1-inch dome tweeters placed 50 degrees off-axis from each other. Switch settings allow the speaker to operate in either a bipole configuration or in opposite polarity as a dipole to create the desired null at the listening area. In the second position there is a circuit to boost bass response, which would normally be lost in the cancellation through the opposite output from the two woofers.

The drivers are mounted in a baffle that has been carefully molded with graceful curves and angles to avoid any sharp reflections. The result is a piece of acoustic artwork that is impressive in both its style and its performance.

Available in three models, the AIM Dipole is destined to become a classic.

AIM Cinema Dipole In-Wall Speakers

AIM Cinema Dipole Five

Order Stock # ASM73551

- Two 5 1/4" Kevlar® Cone Woofers with Phase Plugs
- Two Pivoting 1" Aluminum/Magnesium Dome Tweeters
- Front-Mounted Switches Allow for up to ±3dB of Bass and Treble Adjustment
- Front-Mounted Switches for Bipole or Dipole, QFX & Beam Steering Configuration
- Timbre-Matched to All Five Series Speakers

Bipole Efficiency: 89dB 1W/1m
Dipole Efficiency: 82dB 1W/1m
Power Handling: 5 - 100 Watts
Impedance: 8 Ohms Compatible
Frequency Response: 48Hz - 20kHz ±3dB
Dimensions: (H x W x D) 17 1/2" x 9 1/2" x 3 1/2" (443 mm x 235 mm x 86 mm)
Wall Cut-Out: (H x W) 15 3/8" x 7 1/2" (397 mm x 190 mm)



AIM Cinema Dipole Three

Order Stock # ASM73531

- Two 5 1/4" Aluminum Cone Woofers with Phase Plugs
- Two Pivoting 1" Aluminum Dome Tweeters
- Front-Mounted Switches Allow for up to ±3dB of Bass and Treble Adjustment
- Front-Mounted Switch for Bipole or Dipole, & QFX Configuration
- Timbre-Matched to All Three Series Speakers

Bipole Efficiency: 90dB 1W/1m
Dipole Efficiency: 82dB 1W/1m
Power Handling: 5 - 100 Watts
Impedance: 8 Ohms Compatible
Frequency Response: 50Hz - 20kHz ±3dB
Dimensions: (H x W x D) 17 1/2" x 9 1/2" x 3 1/2" (443 mm x 235 mm x 86 mm)
Wall Cut-Out: (H x W) 15 3/8" x 7 1/2" (397 mm x 190 mm)



AIM Cinema Dipole One

Order Stock # ASM73511

- Two 5 1/4" Injection Molded Graphite Cone Woofers with Phase Plugs
- Two Pivoting 1" Silk Dome Tweeters
- Front-Mounted Switch for Bipole or Dipole Configuration
- Timbre-Matched to All One Series Speakers

Bipole Efficiency: 89dB 1W/1m
Dipole Efficiency: 81dB 1W/1m
Power Handling: 5 - 80 Watts
Impedance: 8 Ohms Compatible
Frequency Response: 55Hz - 20kHz ±3dB
Dimensions: (H x W x D) 17 1/2" x 9 1/2" x 3 1/2" (443 mm x 235 mm x 86 mm)
Wall Cut-Out: (H x W) 15 3/8" x 7 1/2" (397 mm x 190 mm)

